



Quality Products Since 1963

ROOF MASTER "ALL WEATHER" CEMENT PREMIUM GRADE

Description and Specs:

Roof Master Cement is a unique blend of the highest quality asphalt, solvents, choice fibers and specialty surfactants. These products when combined produce a product that has outstanding wet and underwater adhesion. The ability of this product to be applied and perform, in the most severe weather conditions, makes Roof Master Cement the obvious choice when an emergency happens. The flexibility of this product allows it to be used in vertical as well as horizontal applications with equal success. Roof Master Cement is manufactured to a heavy, smooth trowel consistency, which can be applied at a rate of 1/16 to 1/8 in. thick with ease. This material will have an outer shell within hours and cure to a firm shell in 60 days while remaining pliable underneath. Roof Master Cement can be used as an emergency repair or a final solution to problem leaks. Meets ASTM D-4586 Type I and ASTM D-3409. **(Asbestos Free Cement)**

FORMULATED ACCORDING TO SEASON

Uses:

Roof Master Cement is specially formulated for use in damp, wet or underwater situations. When applied in accordance with directions this product will stop leaks in the most severe conditions. Roof Master Cement can be used as a heavy duty flashing cement on walls, skylights, vents, gutters and cornices. This product retains its flexibility even during extreme temperature changes.

Method and Rate of Application:

When applying Roof Master Cement remove all debris from area to be repaired. If surface is wet or under water apply with a trowel, using pressure to ensure a positive bond with the surface. If under water use enough product to stop the leak. To make more of a permanent repair, embed United Asphalt Fabric into cement and reapply Roof Master Cement over the entire area. If on a dry surface apply at a rate of 1/8 in. thick. Keep the container closed to keep product fresh. Do not thin product.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

Cartridge	10 oz.	3.5 gallon	33 lbs.
1 gallon	9 lbs.	5 gallon	45 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com