



Quality Products Since 1963

UNITED ASPHALT ALUMINUM PAINT (NON-FIBERED COATING)

Description and Specs:

United Asphalt Aluminum Paint is formulated by combining a unique blend of asphalts, high flash petroleum solvents and the finest aluminum pigment available. The fusion of these superior materials allows United Aluminum Paint to be mixed and applied more quickly than other products of the same type. The reflectivity of this product, initially, turns back more than 67% of the sun's harmful ultra-violet rays. United Aluminum Paint provides much needed protection to the roof surface and helps control cooling costs in summer. Meets ASTM D-2824 Type I. (**Asbestos Free Aluminum NF Coating**)

Uses:

United Aluminum Paint is used to protect BUR, modified and metal roofs from the heat and ultra-violet rays of the sun. It is recommended to use this product on roofs that are new and smooth because of its lack of fiber reinforcement. United Aluminum Paint should be a part of a building's roof maintenance and energy policy.

Method and Rate of Application: Apply to dry, dirt and oil free surface with a soft brush, roller or spray gun. All blisters and defects should first be fixed using United Asphalt Fabric and Del-Val Flashing Cement. It is recommended, that any weathered surfaces, first be primed with United Asphalt Primer. Be sure to allow primed and repaired surfaces to cure completely before applying United Aluminum Paint, (consult spec sheets for drying times). Mechanically mix before and during application to ensure uniformity of product throughout its use. If applying by brush take care not to overwork product as this may damage the aluminum leaf. When applying product work in one direction to obtain optimum performance. Recommended rate of application is 1/2 to 1 gallon per 100 sq. ft. **United Aluminum Paint should not be applied if dew is present, roof is wet, impending moisture is expected within 24 hours or where ponding water is present. Any of these conditions will have as adverse effect on the performance of the product.**

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

1 gallon	9 lbs.
5 gallon	44 lbs.
55 gallon	484 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com