

United Asphalt, Co.

Quality Products Since 1963

UNITED DAMP-MASTIC BRUSH GRADE "DAMPPROOFING"

Description and Specs:

United Damp –Mastic Brush Grade is a **SOLVENT BASED** fibered damp proofing coating. This product is manufactured to a brush or spray consistency using specialty asphalts, mineral fibers and top quality solvents. This formula is combined to provide a smooth even film over the surface being coated. United Damp-Mastic is made to damp-proof masonry surfaces below grade and has exceptional workability over a wide range of temperatures and conditions. This product can also be used with United Asphalt reinforcing fabric which gives the product more stability during thermal movements. Meets ASTM D-4479 Type I (**Asbestos Free Coating**).

Uses:

United Damp-Mastic Brush Grade is primarily used to damp-proof exterior masonry and concrete walls below grade. It can also be used in conjunction with a water-proofing system where an EPS board and sheet goods are used. *Note EPS board should not be in direct contact with United Damp-Mastic, as this is a solvent based product and may damage the EPS material. Consult manufacturers' recommendations when using in a warranty situation.*

Method and Rate of Application:

Apply to a clean, dry surface. Be sure to sweep away any dust, dirt or loose material from surface being coated. Repair all cracks with United Damp-Mastic Trowel Grade and United Fabric. If surface is very porous it is recommended to prime the face with United Asphalt Primer. Spread United Damp-Mastic Brush Grade with a brush or spray gun at a rate of 4 gallons per 100 sq. ft. Allow product to acquire a film, at least 36 hours, prior to back filling. Be care when back filling, not to damage the coating that has been applied.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater the 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon	42 lbs.
55 gallon	480 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com