



## DEL-VAL FIBERED ALUMINUM ROOF COATING

### Description and Specs:

Del-Val Aluminum Roof Coating is a combination of select asphalt petroleum solvents, reinforcing fibers and the highest quality aluminum pigment. When Del-Val Aluminum Coating is applied correctly it can initially reflect over 65% of the sun's harmful rays. The importance of this coating is evident in the lack of roof deterioration and lower cooling costs in the summertime. Meets ASTM D-2824 Type III. **(Asbestos Free Aluminum FB Coating).**

### Uses:

Del-Val Aluminum Roof Coating is used to protect BUR and Modified from the sun by reflecting its destructive rays. It also is a major component in an environmentally sound building energy policy. With its reflective characteristics it helps to keep building temperatures cooler in summer. Del-Val Aluminum Coating can also be used to beautify metal and weathered roofs or masonry projects.

### Method and Rate of Application:

Apply to a dry, dirt and oil free surface with a soft brush, roller or spray gun. All blisters and defects should first be fixed using United Asphalt Fabric and Del-Val Flashing Cement. It is recommended, that any weathered surfaces, first be primed with either United Asphalt Primer. Be sure to allow primed surfaces to dry completely before applying Del-Val Aluminum Coating, (consult manufacturer spec sheets for drying times). Mechanically mix, to start and also during application, to ensure uniformity of product throughout its use. If applying by brush take care not to overwork product during use, as this may damage the aluminum leaf. When applying product, work in one direction to get optimum brilliance. Recommended rate of application is 1 gallon per 100 sq. ft. on metal surfaces and new APP, and 1.5 to 1.75 gallons per 100 sq. ft. on older weathered roofs. **Del-Val Aluminum Roof Coating should not be applied if dew is present, roof is wet, impending moisture is expected within 24 hours or where ponding water is present. Any of these conditions will have an adverse effect on the performance of the product.**

### Safety:

**CAUTION! COMBUSTIBLE!** KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

**DANGER! HARMFUL OR FATAL IF SWALLOWED!** If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

### Container Sizes:

5 gallon	44 lbs.
55 gallon	484 lbs.

### Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company  
 237 North Grove Street Williamstown Junction, NJ 08009  
 PO Box 291 Cedar Brook NJ  
 856-753-9811 • 800-843-0317 • FX: 856-753-9809  
[www.unitedasphalt.com](http://www.unitedasphalt.com)