



DEL-VAL FIBERED ROOF COATING

Description and Specs:

Del-Val Roof Coating is a combination of asphalt, penetrating oils and reinforcing fibers that are manufactured to a smooth even flowing consistency. The strength of the fibers helps to eliminate running and sagging when exposed to high temperatures. The penetrating oils provide excellent weathering protection to most roof surfaces. Meets ASTM D-4479 Type I. **(Asbestos Free Coating)**

Uses:

Del-Val Fibered Roof Coating is designed for use on flat roof surfaces with positive drainage. It may be used on a variety of surfaces including BUR, metal, SBS Modified or masonry. Del-Val Fibered Roof Coating is used to revitalize old roofs, perform damp-proofing for below grade or can be used in a cold process system with United Fabrics.

Method and Rate of Application:

Apply to a dry, dirt and oil free surface with a brush, roller or spray gun. All blisters and defects should be fixed using United Asphalt Fabric and Del-Val Flashing Cement. When applied to metal roofing an application rate of 1 to 2 gallons per 100 sq. ft. should be used. Composition or felt roofs should be applied at a rate of 3 to 4 gallons per 100 sq. ft. Coverage will depend on porosity of surface.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

1 gallon pails	6 lbs.
5 gallon pails	44 lbs.
55 gallon pails	490 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com