



Quality Products Since 1963

DEL-VAL FOUNDATION COATING "DAMPPROOFING"

Description and Specs:

Del-Val Foundation Coating is a blend of quality asphalts with petroleum distillates. This non-fibered coating provides excellent damp-proofing properties to any surface to which it is applied. Del-Val Foundation Coating requires no thinning or heating and dries, to a glossy, black, smooth, semi-elastic film. It can be used in a wide temperature range thereby allowing contractors to continue working even when weather is below freezing. **(Asbestos Free Coating)**

Uses:

Del-Val Foundation Coating is a black non-fibered coating for application to masonry or brick as a primer, sealer or bonding agent. Its primary use is for exterior below grade masonry walls. It also seals dusty surfaces so that a damp-proof surface is obtained. It can be used to rejuvenate older asphalt roofing materials or as a protective metal coating.

Method and Rate of Application:

Before applying, sweep or brush vigorously to remove all dust, dirt, loose paint or any foreign matter from foundation wall. Stir material to be sure it is uniform consistency. When surface is completely dry apply using a roller, brush or spray gun, apply a continuous coating over the entire area. Be sure to work coating into all cracks and crevices and take note there are no pinholes or voids. Apply to a thickness of 3 to 5 mils. Avoid excess coating which will result in runs and sags. Allow to dry thoroughly before backfilling, usually 5 to 10 hours depending on temperature and film thickness. A rate of 1 to 1.5 gallons per 100 sq. ft. should be used depending on porosity of surface.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon	42 lbs.
55 gallon	480 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com