



PHILADELPHIA FLASHING CEMENT

Description and Specs:

Philadelphia Flashing Cement is elite mastic blended from high quality asphalt, mineral spirits and select fibers. This product is manufactured to a heavy, smooth trowel consistency that can be applied at a rate of 1/16 to 1/8 in. thick with ease. Philadelphia Flashing Cement is designed to stand up to the harshest weather conditions with no sagging, slipping or cracking. This material will cure to a firm outer shell while remaining pliable underneath. Its ultra durability and resistance to weathering are perfect when performing tough vertical or horizontal repairs. Philadelphia Flashing Cement is formulated to three consistencies; Semi, Summer and Winter. Meets ASTM D-4586 Type I. (**Asbestos Free Flashing Cement**)

Uses:

Philadelphia Flashing Cement is specially formulated to be applied to vertical surfaces. This product is primarily used to maintain and repair flashings around parapet walls, chimneys, skylights, downspouts and cornices. It is also useful as a general purpose roof cement for repairing leaks associated with cracks, splits or blisters in BUR, asphalt, shingle and metal roofs.

Method and Rate of Application:

Apply with a trowel, to a clean, dry surface. Spread Philadelphia Flashing Cement to approximately 1/8 in. thickness and work thoroughly into defect. When repairing cracks or blisters apply mastic over the damaged area, embed United Asphalt Fabric for reinforcement. Then, apply another coat of Philadelphia Flashing Cement over the entire area making sure to work back over the unaffected roof area. Care should be taken not to apply too thick, (especially hanging felt on a vertical) as this will put undo stress on the product. One gallon will cover approximately 13 sq. ft. Do not thin product.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater the 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon 42 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com