

United Asphalt, Co.

Quality Products Since 1963

DEL-VAL NON-FIBERED ROOF COATING

Description and Specs:

An asbestos free, non-fibered black asphalt coating with penetrates that help rejuvenate badly deteriorating asphalt roofs. Part of this compound soaks into dried out roofing felts, and part of it remains on the surface to provide water/weather protection (**Asbestos Free Coating**)

Uses:

Use when asphalt felts have dried out as a result of exposure to the sun's rays. Is used to restore roofs, rather than remove them.

Method and Rate of Application:

Before applying coating, remove loose gravel and debris. Apply with brush, roller, or spray equipment. Depending on the roofing surface condition, apply at the rate of 2 to 3 gallons per 100 sq. feet.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon	42 lbs.
55 gallon	475 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com