



UNITED "PREMIUM" FIBERED ALUMINUM COATING

Description and Specs:

United "Premium" Fibered Aluminum Roof Coating is a proprietary mixture of special asphalts, petroleum distillates, high grade aluminum leaf pigment and other mineral fibers that are carefully blended to provide a highly reflective coating. Its metallic brilliance turns back more than 70% of the sun's harmful rays and protects the roof from premature aging and deterioration. United "Premium" Fibered Aluminum Coating contains 3 lbs. per gallon of the finest aluminum pigment available. Meets ASTM D-2824 type III (fibered AF aluminum coating), and ASTM D-962. **(Asbestos Free Aluminum Coating)**

Uses:

United "Premium" Aluminum Coating is the most durable way to protect metal and asphalt roofs. It is a beautifier and rust inhibitor for metal surfaces and is commonly used as a protective topcoat for emulsion and cutback coatings and to extend the life of modified bitumen roofs. With its high reflective properties, United "Premium" Aluminum Coating helps to keep buildings cooler in the summertime thereby saving energy.

Method and Rate of Application:

Roof surface must be clean and free of dirt, dust, oil and other loose particles. All blisters and defects should first be fixed using United Asphalt Fabric and Del-Val Flashing Cement. It is recommended, that any weathered surfaces, first be primed with United Asphalt Primer. Be sure to allow primed and repaired surfaces to completely cure before applying United Aluminum Coating, (consult spec sheets for drying times). Mechanically mix, before and during application, to assure uniformity of product throughout its use. If applying by brush take care not to overwork product, as this may damage the aluminum leafing. When applying product, work in one direction to obtain optimum brilliance.

Recommended rate of application is 1 gallon per 100 sq. ft. on metal surfaces and new APP, and 1.5 to 1.75 gallons per 100 sq. ft. on older weathered roofs. **United "Premium" Fibered Aluminum Coating should not be applied if dew is present, roof is wet, impending moisture is expected within 24 hours or where ponding water is present. Any of these conditions will have an adverse effect on the performance of the product.**

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon	44 lbs.
55 gallon	485 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
 237 North Grove Street Williamstown Junction, NJ 08009
 PO Box 291 Cedar Brook NJ
 856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com