



DEL-VAL ROOF CEMENT (CAP SHEET)

Description and Specs:

Del-Val Roof Cement is a cold process cement that is specifically formulated for Professional Roofers. Del-Val Roof Cement is manufactured from a special adhesive asphalt blend with quick – drying, safe, high flash solvents. The premium flexibility of Del-Val Roof Cement is apparent during freeze thaw cycles. This quality cement has a heavy brush grade consistency that actually grips the felt as it is being applied. **(Asbestos Free Cement)**

FORMULATED ACCORDING TO SEASON

Uses:

Del-Val Roof Cement is designed for use in the application of SIS (half sheet) or 90 lb. (4" selvage rolled roofing). This cement can be used in multi-ply roofing with a polyester mat or felt. Because of Del-Val Cement consistency and extreme bonding quality, it can also be used to seal minor cracks and to rejuvenate an old roof.

Method and Rate of Application:

Apply to a dry, dirt and oil free surface with a brush or serrated trowel. Spread to approximately 1/8 inch thick when applying rolled roofing. Del-Val Roof Cement should be applied at the rate of 1/2 to 2 gallons per 100 square feet.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater the 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon 43 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner.

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com