



UNITED SBS MODIFIED FLASHING CEMENT

Description and Specs:

United Modified Flashing Cement is a blend of select refined asphalts with modified rubber, long fibers and specialty cutbacks. The formulation of these materials in exact proportions creates a heavy bodied trowel grade flashing cement for use with SBS modified roofing. This cement can be used on horizontal surfaces but its real forte lies in its vertical applications. This material will have an outer shell in hours and cure to a firm shell in 60 days while remaining pliable underneath. Meets ASTM D-4586 Type I. **(Asbestos Free Flashing Cement)**

FORMULATED ACCORDING TO THE SEASON

Uses:

United Modified Flashing Cement is specially formulated to adhere SBS modified membranes to vertical surfaces. It can also be used to maintain and repair flashings around chimneys, parapet walls and skylights where modified roofing is applied. This product can also be used on any asphalt based roof to ensure an effective repair.

Method and Rate of Application:

Apply with a trowel to a clean, dry surface. When fixing leaks spread United Asphalt Modified Flashing Cement to approximately 1/8 inch to 1/4 inch thickness and work thoroughly into defect. Imbed United Asphalt Fabric and re-apply cement over the top and back onto the field. If adhering SBS modified membrane to a vertical surface; prime wall with United Asphalt Primer, let dry. Spread United Modified Flashing Cement at 1/4 inch over surface to be coated with membrane and imbed SBS roll. Take notice that the entire roll is in contact with cement and adhesion has begun. Set-up time is approximately 24 hours and cure time is about 7 days, depending on weather conditions. One gallon will cover roughly 13 sq. ft.

Safety:

CAUTION! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. Keep away from heat and flame. Do not heat container or store at temperatures greater the 110° F. Avoid breathing fumes and prolonged contact with skin.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If **swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! When cleaning up, dispose of cans, rags and trowels in accordance with local laws. Keep container closed when not in use to avoid spills.

Container Sizes:

5 gallon 56 lbs.

Clean-up:

Remove product from tools, etc., with kerosene or mineral spirits. Clean hands with a waterless hand cleaner

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 Cedar Brook NJ
856-753-9811 • 800-843-0317 • FX: 856-753-9809
www.unitedasphalt.com